

Surface-mounted luminaire - Micro-prismatic diffuser bottom / top clear - direct distribution / indirect distribution for ceiling lighting

Ultra-flat luminaire housing design, painted extruded aluminium profile, visible installation height 10/24mm; Housing colour silver grey/white aluminium RAL 9006; Direct/indirect light distribution, direct share by means of a microprism made of PMMA, homogeneous light emission through lateral LED light coupling in Light Guide panel and semi-diffuse, reflective white coating, with special decoupling technology for defined ceiling illumination; for VDU workstations, omnidirectional glare reduction according to the current norm DIN-EN 12464-1. Integrated LED driver design. Electrical connection via 3-pole connection terminal with plug-in contacts.. Ceiling attachment rails required for mounting are included in the scope of delivery.

CHARACTERISTICS

Order number	46305024175
EAN number	4020863378104
Commodity code	94051190
Certification mark	IP 20, Protection class I, VDU 65° < 3000, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	48W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	8 pieces/B10, 13 pieces/B16, 13 pieces/C10, 21 pieces/C16
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	5932lm
LED service life	50000h L90/B10 (Tq 25°C)
Luminaire luminous efficiency	125lm/W
UGR lat./long.	16.8 / 16.1

MECHANICS


Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	1558mm x 321mm x 39mm
Weight (net)	5.94kg
Cable entry KE (X/Y)	0mm/0mm
Type of installation	Ceiling-mounted single installation

Dimensions

L	1558 mm	Length
B	321 mm	Width
H	39 mm	Height
A1	900 mm	Mounting distance single mounting
X	0 mm	Distance cable infeed to the center of the luminaire on the X-axis
Y	0 mm	Distance cable infeed to the center of the luminaire on the Y-axis

DEEP-LINK

<https://www.regiolum.de/en/article/46305024175>



Reference	LED 5900lm 830
ηLB	100 %
Φ ↓/↑	74 % / 26 %
UGR lat./long.	16.8 / 16.1
VDU	65° < 3000cd/m²

