

Diffuser luminaire - Opal diffuser - direct/indirect distribution

sheet steel luminaire body, deep drawn; with foam seal and rotary lever locks; Housing colour traffic white RAL 9016; Direct/indirect light distribution using opal acrylic diffuser, with high corner strength drawn from one piece; Electrical connection via 5-pole connection terminal with plug-in contacts..
Note on protection rating: IP50 for ceiling and wall mounting, IP40 for mounting rails and suspended installations.

CHARACTERISTICS

Order number	21100526620
EAN number	4020863351442
Commodity code	94051140
Certification mark	IP 50, Protection class I, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Special properties	Ready for IoT
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)
System output	47W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	12 pieces/B10, 20 pieces/B16, 21 pieces/C10, 33 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	5838lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	126lm/W
UGR lat./long.	23.5 / 21.6

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1515mm x 90mm x 71mm
Weight (net)	2.3kg
Cable entry KE (X/Y)	30mm/0mm
Type of installation	Ceiling-mounted single installation, Ceiling-mounted trunking installation, Mounting rail installation, Wall mounting, Pendant individual mounting

Dimensions

L	1515 mm	Length
B	90 mm	Width
H	71 mm	Height
A1	1100 mm	Mounting distance single mounting
A3	420 mm	Mounting distance between luminaires in a light run arrangement
X	30 mm	Distance cable infeed to the center of the luminaire on the X-axis
Y	0 mm	Distance cable infeed to the center of the luminaire on the Y-axis

DEEP-LINK

<https://www.regiolux.de/en/article/21100526620>



Reference	LED 5800lm 830
ηLB	100 %
Φ ↓/↑	82 % / 18 %
UGR lat./long.	23.5 / 21.6

