

LED wall and surface-mounted luminaire - Matt diffuser - direct/indirect distribution

Round LED wall and surface-mounted luminaire, IP40. With a very flat, slightly rounded polycarbonate housing, including anti-theft device and insect protection ring. Housing colour similar to RAL 9003, The time-saving installation is by means of an easy-to-use click-fit system on the luminaire base made of sheet steel. Plug-and-play contact when the luminaire is opened; Housing colour white, similar to RAL 9003; diffuser with matt opal surface made of PMMA, cleaning-friendly. This produces a very homogeneous light in combination with LED individual lenses. Electrical connection via 3-pole connection terminal with plug-in contacts..

CHARACTERISTICS

| | |
|-------------------------------|--|
| Order number | 21906014180 |
| EAN number | 4020863394463 |
| Commodity code | 94051140 |
| Certification mark | IP 40, Protection class I, ENEC10 VDE, Heat filament test 650°C, F, Indoor, CE |
| Impact resistance (IK rating) | IK03 (10°C bis 35°C) |
| Ambient temperatur | ta 10°C to 35°C |
| Warranty period | 5 years |
| State funding programs | BEG - Federal funding for efficient buildings (valid only for Germany) |

ELECTRICAL ENGINEERING

| | |
|--------------------------------------|--|
| Controller | Electronic driver (1 pcs.) |
| System output | 23W |
| Mains voltage | 230V/50Hz |
| Circuit breakers (inrush current) | 13 pieces/B10, 22 pieces/B16, 22 pieces/C10, 37 pieces/C16 |
| Energy efficiency class/light source | C |

LIGHTING TECHNOLOGY

| | |
|-------------------------------|---|
| Placement | LED, Colour rendering/Light colour CRI ≥ 80 / 4000K |
| Colour tolerance (MacAdam) | 5SDCM |
| Nominal luminous flux | 2903lm |
| LED service life | 50000h L80/B10 (Tq 35°C) |
| Luminaire luminous efficiency | 129lm/W |
| UGR lat./long. | 23.0 / 23.1 |

MECHANICS


| | |
|----------------------|---|
| Housing colour | white, similar to RAL 9003 |
| Dimensions (LxWxDxH) | 380mm x 69mm |
| Weight (net) | 1.82kg |
| Cable entry KE | See mounting instructions |
| Type of installation | Ceiling-mounted single installation, Pendant individual mounting, Wall mounting |

Dimensions

| | | |
|---------------|--------|---|
| H | 69 mm | Height |
| D | 380 mm | Diameter |
| A1 | 208 mm | Mounting distance single mounting |
| A1 alternativ | 180 mm | Mounting distance single mounting (alternatively) |

DEEP-LINK

<https://www.regiolum.de/en/article/21906014180>



| | |
|----------------|----------------|
| Reference | LED 2900lm 840 |
| ηLB | 100 % |
| Φ ↓/↑ | 85 % / 15 % |
| UGR lat./long. | 23.0 / 23.1 |

