

reloUP

Surface-mounted downlight


Timeless simplicity



REGIOLUX

relo-UP

Surface-mounted
downlight



Highlights

- Classic downlights for stylish ceiling surface mounting
- Quick-mount plate with Snapfix quick-release fastener
- Robust, die-cast housing, driver wired ready for operation
- Feed-through wiring

Areas of application

- Staircases, corridors
- Rest areas and guest rooms
- Wellness facilities, treatment rooms
- Foyers and lobbies
- Waiting areas
- Secondary rooms

Practical details for the mounting plate:
Snapfix quick-release fastener and safety cable



relo-UP	Configuration	Control gear	DxH	Order number	lm/W	P _{sys} [W]	kg
relo-up-RDAS-0/140	LED 1000 830	ED	140 x 115	3769 1114 140	73	14	1,03
		DALI2 ¹⁾	140 x 115	3769 1116 640	73	14	1,03
	LED 1100 840	ED	140 x 115	3769 1104 140	82	14	1,03
		DALI2 ¹⁾	140 x 115	3769 1106 640	82	14	1,03
relo-up-RDAS-0/190	LED 1700 830	ED	190 x 120	3769 2114 140	86	20	1,74
		DALI2 ¹⁾	190 x 120	3769 2116 640	86	20	1,74
	LED 1900 840	ED	190 x 120	3769 2104 140	97	20	1,74
		DALI2 ¹⁾	190 x 120	3769 2106 640	97	20	1,74
relo-up-RDAS-0/230	LED 2700 830	ED	230 x 115	3769 3114 140	95	28	3,15
		DALI2 ¹⁾	230 x 115	3769 3116 640	95	28	3,15
	LED 3000 840	ED	230 x 115	3769 3104 140	107	28	3,15
		DALI2 ¹⁾	230 x 115	3769 3106 640	107	28	3,15

¹⁾Luminaires suitable for IoT (Internet of Things):